



DOUBLE-GLASS BIFACIAL N-TYPE 430~440 Watt



Bifacial Mono Module

Capable of generating power at back side, at least 80% efficiency of the front side



Anti-PID (potential induced degradation)

Passed anti-PID test under 85°C damp heat 85% relative humidity for 192 hours



Great Durability against extreme conditions

Passed salt mist corrosion test, ammonia corrosion test, dust & sand test, fire test, all certified by TÜV



Lower LCOE

Lower shading and resistive loss
Lower temperature coefficient



Outstanding mechanical load resistance

2400 Pa wind load, 5400 Pa snow load



15-year product warranty

30-year linear power output



CEC Listed



IEC 61215, IEC 61730

ISO 9001: 2015 (Quality management systems)

ISO 14001: 2015 (Environmental management systems)

ISO 45001: 2018 (Occupational health and safety)

UNI 9177 la CLASSE DI REAZIONE AL FUOCO: 1



Add: No. 238 Yunlin Middle Road, Wangchun Industrial District, Ningbo China

Tel: +86-574-28828939

Email: sales@ulsolar.com.cn

Fax: +86-574-28828997

Web: www.ulicasolar.com

TOPCon(N TYPE) 430~440Watt



ELECTRICAL SPECIFICATIONS

Module Type	UL-430M-108ADGN		UL-435M-108ADGN		UL-440M-108ADGN		
	STC* NOCT*		STC* NOCT*		STC* NOCT*		
Maximum Power (Pmax)	W	430	326	435	330	440	333
Maximum Power Voltage (Vmp)	V	31.81	29.27	31.91	29.36	32.01	29.61
Maximum Power Current (Imp)	A	13.52	11.13	13.63	11.23	13.75	11.26
Open-circuit Voltage (Voc)	V	39.24	35.71	39.39	35.84	39.54	35.98
Short-circuit Current (Isc)	A	13.89	11.20	13.95	11.25	14.01	11.30
Module Efficiency STC	%	22.02		22.28		22.53	
Operating Temperature	-40°C~85°C						
Maximum system voltage	DC1500V(IEC)						
Maximum series fuse rating	30A						
Power tolerance	0~+5Watt						
Temperature coefficients of Pmax	-0.29%/°C						
Temperature coefficients of Voc	-0.25%/°C						
Temperature coefficients of Isc	0.046%/°C						
Nominal operating cell temperature (NOCT)	43±2°C						

*STC : Cell temperature: 25°C, Irradiance: 1000 W/m², Air mass: 1.5G
 *NOCT: Air temperature: 20°C, Irradiance: 800 W/m², Air mass: 1.5G, Wind speed: 1 m/s

SPECIFICATIONS



Cell Type	N type Mono-crystalline
No. of cells	108(6×9×2)
Dimensions	1722*1134*30mm
Weight	23.5kg
Glass	2.0mm+2.0mm, Anti-Reflection Coating, High Transmission, Low Iron, Tempered Glass
Junction Box	IP68, 3 diodes
Connector	MC4 Compatible
Cable Length (including Connector)	4mm² Landscape: (+)1100/(-)1100mm or Customized Length
Packaging Configuration	Two Box=One Pallet 36pcs/Box, 72pcs/Pallet, 936pcs/40HQ Container

Electrical characteristics with different rear side power gain (reference to 440 W front)

Pmax/W	Voc/V	Isc/A	Vmp/V	Imp/A	Pmax gain
440	39.54	14.01	32.01	13.75	0%
462	39.54	14.71	32.01	14.44	5%
484	39.54	15.41	32.01	15.13	10%
506	39.54	16.11	32.01	15.81	15%
528	39.54	16.81	32.01	16.50	20%
550	39.54	17.51	32.01	17.19	25%
572	39.54	18.21	32.01	17.88	30%

I-V CURVE

I-V characteristics at different irradiatio (reference to 440 W)



I-V characteristics at different temperature

