


MONO-FACIAL MODULE N-TYPE 610~625 Watt

TOPCon



Cutting Free Technology
Minimized micro-crack



Anti-PID (potential induced degradation)
Passed anti-PID test under 85°C damp heat
85% relative humidity for 192 hours




Great Durability against extreme conditions
Passed salt mist corrosion test, ammonia corrosion test
dust & sand test, fire test, all certified by TUV



Lower LCOE
Lower shading and resistive loss
Lower temperature coefficient



Outstanding mechanical load resistance
2400 Pa wind load, 5400 Pa snow load



15-year product warranty
30-year linear power output



CEC Listed



IEC 61215, IEC 61730

ISO 9001: 2015 (Quality management systems)

ISO 14001: 2015 (Environmental management systems)

ISO 45001: 2018 (Occupational health and safety)

UNI 9177 la CLASSE DI REAZIONE AL FUOCO: 1



Add: No. 238 Yunlin Middle Road, Wangchun Industrial District, Ningbo China

Tel: +86-574-28828939

Email: sales@ulsolar.com.cn

Fax: +86-574-28828997

Web: www.ulicasolar.com

ELECTRICAL SPECIFICATIONS

Module Type	UL-610M-144CHVN			UL-615M-144CHVN		UL-620M-144CHVN		UL-625M-144CHVN	
	STC* NOCT*			STC* NOCT*		STC* NOCT*		STC* NOCT*	
Maximum Power (Pmax)	W	610	462	615	466	620	470	625	474
Maximum Power Voltage(Vmp)	V	44.42	40.87	44.62	41.05	44.82	41.23	45.02	41.42
Maximum Power Current(Imp)	A	13.73	11.31	13.78	11.35	13.83	11.39	13.88	11.44
Open-circuit Voltage(Voc)	V	52.42	47.70	52.62	47.88	52.82	48.07	52.85	48.09
Short-circuit Current(Isc)	A	14.65	11.82	14.70	11.86	14.80	11.94	14.81	11.95
Module-Efficiency STC	%	22.58		22.77		22.95		23.14	
Operating-Temperature					-40℃~85℃				
Maximum system voltage					DC1500V(IEC)				
Maximum series fuse rating					25A				
Power tolerance					0~+5Watt				
Temperature coefficients of Pmax					-0.29%/℃				
Temperature coefficients of Voc					-0.25%/℃				
Temperature coefficients of Isc					0.046%/℃				
Nominal operating cell temperature (NOCT)					43±2℃				

*STC:Cell temperature:25°C,Irradiance:1000W/m²,Air mass:1.5G



*NOTC:Air temperature:20°C,Irradiance:800W/m²,Air mass:1.5G,Wind speed:1m/s

SPECIFICATIONS



Cell Type	N type Mono-crystalline
No. of cells	144(6×12×2)
Dimensions	2382*1134*35mm
Weight	27.8kg
Front Glass	3.2mm,Anti-Reflection Coating,High Transmission,Low Iron,Tempered Glass
Junction Box	IP68,3diodes
Connector	MC4 Compatible
Cable Length (Including Connector)	4mm ² Landscape:(+)1400mm/(-)1400mm or Customized Length
Packaging Configuration	Two Box=One Pallet 31pcs/Box,62pcs/Pallet,620pcs/40HQ Container

I-V CURVE

I-V characteristics at different irradiancies (reference to 615 W)



I-V characteristics at different temperature



Specifications included in this datasheet are subject to change without notice.

Ulica Solar reserves the right of final interpretation.

Version No.: UL-2382-144CHVNBBC-35-EN-V1.1